

# LOFTNESS

ROCKPICKERS

## Skid-steer Mounted Rockpicker

Picks Rocks and Debris  
from 2 inches (5 cm)  
to  
2 feet (61 cm) in diameter



### Advantages

- \* Never Pick Up Rocks by Hand Again
- \* For Use in: Agriculture, Commercial, Industrial and Landscaping
- \* Picks Up: Rocks, Rubble, Logs, Firewood, Bricks, Blocks and Other Debris
- \* Four Sizes to Choose From: 48, 60, 72 & 84 inch (1.22, 1.52, 1.83 & 2.13m)
- \* Front-mounted, Front-dumping
- \* Dumps Rocks Directly Into Trucks Quickly and Safely
- \* Requires Only 6 gpm Hydraulic Flow

For More Info Go To:  
[rockpicker.com](http://rockpicker.com)

# 48, 60, 72 & 84 inch Models

(1.22, 1.52, 1.83 & 2.13 meter)

	480	600	720	840
Capacity	1/2 cubic yard (.38 cu.m)	5/8 cubic yard (.48 cu..m)	3/4 cubic yard (.57 cu.m)	1 cubic yard (.76 cu.m)
Opening Width	48 inches (1.22 m)	60 inches (1.52 m)	72 inches (1.83 m)	84 inches (2.13 m)
Opening Height	24 inches (.61 m)	24 inches (.61 m)	24 inches (.61 m)	24 inches (.61 m)
Weight	855 pounds (388 kg)	1005 pounds (456 kg)	1150 pounds (522 kg)	1426 pounds (647 kg)
Recommended Skid-steer Lifting Capacity	1800 pounds (816 kg)	2250 pounds (1020 kg)	2700 pounds (1224 kg)	New Holland Bi-directional



US Patent  
# 5682953

Warning: Some Illustrations May Show Safety Shields Removed for a Better View.  
Equipment Should Never be Operated with Safety Shields Removed.  
Note: All Information and Specifications are Subject to Change without Notice.


Canada Patent  
# 2198785

## Features

- \* 2 inch (5 cm) to 24 inch (61 cm) Rock Sizes
- \* 360 degree Bi-directional Hydraulic Reel
- \* 6 GPM (22 lpm) Hydraulic Requirement
- \* 1-3/4 inch (44 mm) Reel Bearings
- \* Universal Skid-steer Mount (except 840)
- \* Grated Bottom with 2 inch (5 cm) Openings
- \* Picks Rocks, Concrete, Rubble, Wood
- \* 1 inch High Carbon Steel Tines
- \* # 60HD Roller Chain on Hydraulic Reel
- \* Front Dumping like a Conventional Bucket
- \* 3/16 inch (44 mm) Side Plates (1/4 in. (6.3 mm) on 840)
- \* 1/4 inch (6.3 mm) Back Plate (5/16 in. (8 mm) on 840)
- \* Protective Screen for Operator Protection
- \* Charcoal Grey Paint

**LOFTNESS**

ATTACHMENTS  
LOFTNESS.COM



650 South Main Street - PO Box 337 - Hector, MN 55342 USA

Toll Free US and Canada: 800-828-7624  
International: 320-848-6266  
Sales Fax: 320-848-6269  
New Parts Fax: 320-848-6055  
E-mail Address: Info@loftness.com

Published  
January 2003