

# AVANT<sup>®</sup> 700



## Outstanding handling capacity

- ✓ Cab options L/LX/DLX available, DLX also with A/C
- ✓ Easy to transport with car trailer
- ✓ Optidrive™ drive circuit gives more power for the drive and hydraulic attachments

The Avant 700 series offers strong and versatile multi-use loaders for jobs where high lift capacity and/or drive speed is needed, yet at the same time the machine can be as compact as possible. The 700 series is the perfect tool for street cleaning and other property maintenance tasks on narrow streets and yards, handling paving stones, moving materials on construction sites, and many other applications. Easy transportation with a car trailer and a high drive speed enable quick transfers between work sites.

High flow auxiliary hydraulics runs all Avant attachments which further increases the versatility of the machine.

A wide range of options increase operator comfort as well. The 700 series can be fitted with all cab options and A/C, which ensures ideal conditions for a full day's work.

While Avant loaders are made as compact as possible, the reach and lift height do not suffer from it. Avant's telescopic boom makes it possible to have a very compact machine with a great outreach and lift capacity. When the telescopic boom is retracted, it is possible to lift heavier loads. With the boom fully extended, the reach and lift height are unparalleled. In many cases it is possible to load a trailer from one side thanks to the outreach of the telescopic boom while still maintaining excellent visibility.



**40.6 - 57.1 in**



**3970-4640 lb**



**122 in**



**3810 lb**



**26-57 hp  
diesel**



**0-16.2 MPH**

# specifications



## height with cab

Wheel size	26x12.00-12 320/60-12	320-55/15*
Cab L	81.1 in	82,4 in
Cab LX	81.8 in	83.1 in
Cab DLX	82.9 in	84.2 in
Cab DLX with air conditioning on the roof	88.2 in	89.6 in

\*) With 400/50-15 machine is 1.2 in higher

## machine width

Wheel size	Profile	Machine width	
		735/755i	760i
27x8.50-15	TR	40.6 in	42.5 in /46.6 in
26x12.00-12	TR or grass	50.8 in	53.1 in
320/60-12 HD	TR	50.8 in	53.1 in
320/55-15	TR or grass	51.4 in	53.5 in
400/50-15	TR or grass	-	57.1 in

Model	AVANT 735	AVANT 755i	AVANT 760i
Length	120.9 in	120.9 in	120.9 in
Width (standard tires)	51 in	51 in	57.1 in
Height (standard tires)	82.3 in	82.3 in	84.3 in
Weight, starting from	3970 lb	4420 lb	4640 lb
Standard tires	26/12.00-12 Grass, 320/60-12 Tractor		400/50-15 TR or grass
Transmission	hydrostatic Avant Optidrive™	hydrostatic Avant Optidrive™	hydrostatic Avant Optidrive™
Pulling force	2650 lbf	2990 lbf	3600 lbf
Drive speed	8.7 MPH	10.6 mph	16.2 mph
Auxiliary hydraulics	13.2 gal/min 2900 PSI	21.1 gal/min 3260 PSI	21.1 gal/min 3260 PSI
Turning radius (inside/outside)	49.2 / 105.3 in	49.2 / 105.3 in	49.2 / 105.3 in
Lifting height	122.0 in	122.0 in	122.0 in
Tipping load	3810 lb	3810 lb	3810 lb
Max. breakout force at 20 in	3750 lbf	3750 lbf	3750 lbf
Engine make and type	Kubota V1505, 4-cyl.	Kohler KDI 1903 TCR	Kohler KDI 1903 TCR
Engine output	26 hp	57 hp	57 hp
Maximum torque	69 lbf-ft @ 1700 rpm	166 lbf-ft @ 1500 rpm	166 lbf-ft @ 1500 rpm
Fuel	Diesel	Diesel	Diesel