

TERRAGATOR

TG7300C / TG8300C TERRAGATOR CHASSIS (2019)

Parts and Service Guide



TERRAGATOR Specifications*

ENGINE	TG7300C	TG8300C
Make	AGCO Power	AGCO Power
Type	AP84-4	AP84-4
Number of Cylinders	6	6
Displacement	8.4 L (513 CID)	8.4 L (513 CID)
Horsepower	332 HP (247 kW) @ 2,100 rpm	365 HP (272 kW) @ 2,100 rpm
Peak Horsepower Torque	363 HP (270 kW) @ 1,900 rpm 1,180 ft-lbs (1,600 N-m) @ 1,500 rpm	393 HP (293 kW) @ 1,900 rpm 1,180 ft-lbs (1,600 N-m) @ 1,500 rpm
rorque	1,100 11-105 (1,000 N-111) @ 1,500 1pi11	1,100 11-105 (1,000 N-111) @ 1,500 1p111
TRANSMISSION		
Type Forward Speed (high/low)	AGCO ML-260 Continuously Variable Transmission 41 mph / 23 mph (67 kmh / 37 kmh)	AGCO ML-260 Continuously Variable Transmission 41 mph / 23 mph (67 kmh / 37 kmh)
	, , , , , , , , , , , , , , , , , , ,	
DRY SYSTEM AirMax Precision**	Single bin, 355 cu.ft. (10.1 m³)	Single bin, 355 cu.ft. (10.1 m³)
AirMax Precision 2**	olligio bill, coo da.r.: (ro.r III /	Adjustable, split bin, 345 cu.ft. (9.8 m³)
Soilection Twin Bin***		Two bins, 320 cu.ft. (9.1 m³)
New Leader NL4500	Single bin, MultApplier insert, MultiBin,	Single bin, MultApplier insert, MultiBin,
	up to 331 cu.ft. (9.3 m³)	up to 331 cu.ft. (9.3 m³)
New Leader NL5000	Single bin, MultApplier insert, MultiBin,	Single bin, MultApplier insert, MultiBin,
	up to 331 cu.ft. (9.3 m³)	up to 331 cu.ft. (9.3 m³)
LIQUID SYSTEM	TG7300C/TG8300C	
Capacity	1,800 gal. (6,814 L)	
Pump	260 GPM (984 LPM)	
Booms	60/80 ft. (18/24 m) fold-over boom 80 ft. (24 m)	
Breakaway, Full Boom	Hydraulic, resettable	
Breakaway, Boom Tip	Mechanical, spring return	
Height / Tilt Adjustment	Hydraulic	
Nozzle Spacing	30 in. (0.76 m) or 60 in. (1.52 m)	0.5
Total Spray Width	82.5 ft. (25.1 m) on 30 in. centers; 85 ft. (25.9 m) on 6	U In. centers
AIR SYSTEM		
Compressor	Engine-mounted	
Governor	120 psi (8.2 bar)	
CFM Pagaryair	14.1 cfm (6.7 L/s)	
Reservoir	Dual	
AXLES		
Front	3.75-indiameter (9.5 cm) freewheeling, cold-rolled s	olid steel
Rear	Wide track 42,000-lb. rating with flotation tires	
TIRES		
Standard	Goodyear® Radial 1000/50R25	
Optional	Michelin® Radial 1000/50R25	
SUSPENSION		
Туре	Rigid rear axle to frame mount	

TERRAGATOR Specifications* (cont.)

STEERING TG7300C/TG8300C

Type Dynamic load sense

WEIGHTS

Rated Capacity Front 14,000 lbs. (6,350 kg) Rated Capacity Rear 42,000 lbs. (19,050 kg)

APPLICATION CAB

Glass Area / Floor Area 58 sq.ft. (5.4 m²) / 14 sq.ft. (1.39 m²)

Cab Suspension Air-ride cab

Radio AM/FM / stereo, USB MP3-compatible, Weather band, Bluetooth® with mic., Opt. SiriusXM®

HVAC / Filtration Automatic temperature control / 3-level activated carbon

Standard Seat Cloth with air-ride suspension

Optional Seat Leather heated-vented with air-ride suspension

FLUID CAPACITIES

Fuel 165 gal. (625 L)
DEF (Diesel Exhaust Fluid) 15 gal. (56.8 L)
Engine Coolant 8 gal. (30.3 L)
Engine Oil 6 gal. (22.7 L)
Transmission Oil 14 gal. (53 L)
Hydraulic Reservoir 12 gal. (46 L)

CONTROLLERS

Controllers Available Raven Viper 4+

^{*} Specifications are manufacturer's estimates at time of publication and are subject to change without prior notification. Actual weight will vary depending on optional equipment.

^{**} Single 40 cu.ft. (1.13 m³) granular bin available


^{***} Dual 25 cu.ft. (0.7 m³) granular bins available

TERRAGATOR Parts List

ITEM	PART NUMBER	ΩТΥ	DESCRIPTION	TECHNICAL SPECIFICATION
1	568310D1	1	Air Filter Element — Primary Air Filter	
2	568311D1	1	Air Filter Element – Safety	
3	72311028	1	Filter Element — Transmission High Pressure	
	72312070	1	Oil Filter Element – Transmission Suction	
4	AG520617	1	Suction Strainer – Hydraulic	2.5"
5	532430D1	1	Filter Element — Hydraulic	
6	556653D1	1	Cab Filter	
7	556654D1K	1	Cab Filter — Carbon	
8	AG718281	1	Air Filter Element – Cab	Particle
9	V836379588	1	Engine Oil Filter	
10	AG524540	1	Inline Strainer	100 Mesh
11	V837091129	1	Fuel Filter Kit	
	3905873M91	1	Fuel Filter Element – Water Separator	
12	567109D1	1	Belt – A/C Belt	1218 mm
	V685122255	1	Multi-Ribbed Belt – Fan Belt	
13	V837079423	1	DEF Filter	
14	AG330202	1	Filter – Air Dryer	

TO ORDER:

TERRAGATOR Machine Diagram





TERRAGATOR Service Guide

	INTERVAL								PAR	TS AND LUBRICANTS			
SERVICE ITEMS	Initial 100	100	250	400	500	800	1000	2000	Annual	Comprehensive	Part # / Charge Code	Оty	Description
Clean the cooling system (from outside)	Х	Х		Χ	Х	Χ	Χ	Χ		Х			
Check the condition of the belt	X	Х		Χ	Χ	Χ	Χ	Χ		Х			
Change the engine oil and filter				Χ		Χ		Х	Х	X	V837074523 SAMPLE	1 6 1	Engine Oil Filter AGCO 15W-40 CI-4 ENGINE OIL GAL Sample
Change the fuel filters						Χ			Х	X	V837091129 3905873M91	1 1	Fuel Filter Kit Fuel Water Separator
Check/administer engine software update				Χ		Χ		Χ		Х			
Check the torque on rear and front wheel nuts	X	Х		Χ	Χ	Χ	Χ	Χ		Χ			
Check the torque on the charge air hose clamps and hose from the turbo to the CAC	Х					**************************************	Х	Х	Χ	X			
Replace the inline fuel strainer	Х						Χ	Χ	Х	Х	AG524540	1	Inline Strainer
Lubricate the tag axle fittings (if equipped)		Ser	vice Item	not incl	uded in	PM – cr	eate sep	arate se	gment for s	service			
Lubricate front wheel bearings	Х	Х	Χ	Χ	Χ	Χ	Χ	Χ		Χ	79017915	1	MOLY EP Grease
Check the rear axle mounting bolts, tighten to torque of 424 lbf ft	Х						Х	Х	Χ	X			
Check brake air lines	X	Х	Χ	Χ	Χ	Χ	Χ	Χ		Χ			
Replace the hydraulic oil filter	Х						Χ	Χ	Х	Χ	587603D1	1	Hydraulic Filter
Replace the hydraulic oil							Х	Х	Χ	X	SAMPLE"	14 1	AGCO 821XL 10W-30 PERMATRAN GAL Sample
Replace the CVT high pressure filter	Х						Х	Х	Х	X	72311028 72313495"	1 1	High Pressure Filter O-Ring
Replace the pressure washer pump oil	X				Χ		Χ	Χ	Χ	Х		Se	e lubricant table below
Check front and rear cab mounts	X	Х		Χ	Χ	Χ	Χ	Χ		Χ			
Lubricate the steering cylinder ends	Х	Х		Χ	Χ	Χ	Χ	Χ		Х	79017915	1	MOLY EP Grease
Drain the water and sediment out of the fuel tank	Х	Х		Χ	Χ	Χ	Χ	Χ		X			
Check the differential and planetary oil level		Х		Χ	Χ	Χ		Χ					
Drain the water and sediment out of the fuel tank	X	Х		Χ	Χ	Χ	Χ	Χ		X			
Check the differential and planetary oil level		Х		Χ	Χ	Χ		Χ					
Replace the differential and planetary oil	X						Х	Х	X	X	79014722 AG331201 AG331200 SAMPLE	3 1 1 3	AGCO Gear Lubricant/ Axle Oil 2.5 GAL O Ring O Ring Samples
Clean the differential breather	X	Х		Χ	Х	Χ	Χ	Χ		X			
Check the tag axle bearing bolt torque (if equipped)									gment for s				
Check brakes manual slack adjusters (if equipped)		Ser		not incl	:	PM – cr			gment for s	service			
Inspect and clean the cab air filters			Χ		Х		Χ	Χ					
Lubricate grease fittings on driveline Check the clutch master cylinder fluid; check for correct operation			Х	Х	Х	Χ	Х	X		X X	79014728	1	Multi-Purpose Lithium II Grease
Replace the air dryer filter					Χ		Χ	Х		Χ	AG330202	1	Air Dryer Filter
Lubricate the brake slack adjuster on the rear axle					X		X	X		X	79017915	1	MOLY EP Grease
Check the engine-to-frame ground connections					Х		X	X		X			
Check driveline U-joints					Χ		Χ	Χ		X			
Replace the receiver-dryer (A/C system)							Χ	Х	Х	Х	593052D2	1	A/C Receiver Drier
Replace the primary engine air filter							Χ	Χ	Х	Х	568310D1	1	Primary Engine Air Filter
Replace the pressure washer strainer							Χ	Χ	Х	X	AG513640	1	Inline Pressure Washer Strainer
Replace the cab air filters									Х	X	556653D1 556654D1K AG718281	1 1 1	Cab Filter Cab Carbon Filter Particle Filter

LUBRICANTS								
Component	Oil type/Class	Viscosity	US GAL	# of Components	Part # / Charge Code	Description		
Rear axle differential and planetary	GL-5	80W-90	6.5	1	79014722	AGCO Gear Lubricant/ Axle Oil 2.5 GAL		
Hydraulic system	Permatran 821XL	10W-30	13.5	1		AGCO 821XL 10W-30 PERMATRAN GAL		
Transmission	Permatran 821XL PLUS	15W-40	15.1	1		AGCO 821XL PLUS 15W-40 TRAN OIL GAL		
Engine oil	CJ-4	15W-40	6	1		AGCO 15W-40 CI-4 ENGINE OIL GAL		
Grease fittings	high temp moly-lithium base grease			1	79017915	MOLY EP Grease		
Pressure wash pump	NON-Detergent oil	30W	0.0935	1				
Grease fittings on driveline	high temp NLGI #2 multi-purpose moly-free lithium grease				79014728	Multi-Purpose Lithium II Grease		
CVT clutch oil	Pentosin CHF 11S							
Engine coolant	50/50 water & ethylene glycol without stop leak additive with SCA	50/50	8.2	1	ZXRU1	PREMIX COOLANT		