

# W530A ROAD WIDENER



## ONE TOUCH HANDLING.

When it comes to placing the right amount of material at the correct grade and slope in one pass, whether on a shoulder or elsewhere, the best equipment for the job is a Weiler road widener.



## MATERIAL DELIVERY.

A 3.5 yd<sup>3</sup> (2.6 m<sup>3</sup>) hopper means fewer truck exchanges during the workday. The 24" (610 mm) wide belt and 400 fpm (121 mpm) belt speed provides quick placement of materials to either side of the machine. The hydraulically adjustable dump hopper accommodates varying trucks.



## PRECISE STRIKE-OFF

25" (635 mm) tall strike-off tools widen from 1' (.3 m) to 10' (3 m) and are capable of placing material up to 12" (305 mm) above and below grade. Multiple tool sizes plus hydraulically adjustable tools ensure precise strike-off and can be set to exact grade and slope specifications.




## RELIABLE POWERTRAIN.

The W530A has the power to push. The two 2-drive version features a Cat<sup>®</sup> C3.4B Tier 4 engine with 120 hp (89 kW) while the 4-wheel drive features 137 hp (102 kW). Hydrostatic drive with 2-speed motor and 2-speed gearbox delivers 350 fpm (106 mpm) working speed and 12 mph (19 km/hr) transport speed.



## VISIBILITY AND CONTROL.

All controls are located on a single panel within easy reach of the operator. Sliding control console enhances operator ease of use, enabling both left and right side access to all machine controls. The operator is located back from the dump hopper and toward the outer edge of the machine for increased visibility.



## FAST SERVICE.

Self cleaning pulleys minimize material build-up and large doors enable easy access to engine and machine components. Built-in tool storage locations provide home spots for all components needed on the job. Caterpillar dealer service and support keep your machine up and running with limited down time.

# W530A SPECIFICATIONS

<b>WEIGHT</b>	26,327 lb	11 941 kg	<b>HOPPER CAPACITY</b>	3.5 yd <sup>3</sup>	2.6 m <sup>3</sup>	<b>ENGINE</b>	Cat® C3.4B/C4.4 Tier 4
<b>OPT. REAR WEIGHT</b>	2,300 lb	1043 kg	<b>CONVEYOR LENGTH</b>	10'	3048 mm	<b>TURNING RADIUS</b>	15' 6" 4.7 m
<b>LENGTH</b>	22' 4"	6807 mm	<b>CONVEYOR WIDTH</b>	24"	610 mm	<b>REAR STEER TURN RADIUS</b>	8' 2.4 m
<b>WIDTH</b>	10'	3048 mm	<b>BELT SPEED</b>	400 fpm	121 mpm	<b>FUEL CAPACITY</b>	74 gal 280 L
<b>HEIGHT</b>	7' 8"	2336 mm	<b>MAX WORKING SPEED</b>	350 fpm	106 mpm	<b>HYDRAULIC CAPACITY</b>	60 gal 227 L
<b>WHEELBASE</b>	130"	3302 mm	<b>TRANSPORT SPEED</b>	12 mph	19 km/hr		

## POWERTRAIN

Cat® C3.4B Tier 4 Engine, 120 hp (89 kW)  
Cat® C4.4 Tier 4 Engine, 137 hp (102 kW) w/ 4-wheel drive  
Front wheel hydrostatic drive standard  
4-wheel hydrostatic drive option  
2-speed motor  
2-speed gearbox  
350 fpm (106 mpm) max working speed  
12 mph (19 km/hr) transport speed  
Differential lock on front axle  
2-wheel steering standard  
15' 6" (4.7 m) standard turning radius  
4-wheel steer option  
8' (2.4 m) turning radius w/ 4-wheel steer  
Fail safe parking brake  
385/65R x 22.5, 16 ply tires

## OPERATING ENVIRONMENT

Tool free sliding control console  
Access to all machine controls from console  
Seats located to the outside of machine  
Wrap around safety rails and kick plates  
USB port  
Easy storage of tools for transport

## MATERIAL DELIVERY

3.5 yd<sup>3</sup> (2.6 m<sup>3</sup>) hopper capacity  
9' 4" (2844 mm) dump hopper opening  
Hydraulically operated dump hopper  
10' (3048 mm) long, 24" (610 mm) wide chain-driven conveyor  
Left or right material discharge  
400 fpm (121 mpm) belt speed  
6" (152 mm) conveyor shift in either direction  
Adjustable push roller

## SALES AND SERVICE

Sold and serviced exclusively through Caterpillar dealers worldwide.

## TOOLING

1' (0.3 m) to 10' (3 m) widening width  
12" (305 mm) above and 12" (305 mm) below grade  
25" (635 mm) tall strike-off tools  
1' (.3 m), 2' (.6 m) and 3' (.9 m) standard tool  
6' (1.8 m) and 2'-3' (.6 m - .9 m) adjustable tool option  
3'-5' (.9 m - 1.5 m) adjustable tool option  
Standard tool tray  
Side-mounted tool box for accessories

## SERVICE/MAINTENANCE

Multiple engine access doors  
Easily accessible battery compartment  
Self cleaning pulleys minimize material build-up  
Braided electrical harnesses and sealed connections

## OPTIONAL EQUIPMENT

Rear wheel drive and steering  
Rear steer  
Truck hitch  
Hydraulically adjustable push roller  
Hydraulically raised and lowered front hopper  
Enclosed cab with heat and a/c  
Foot pedal conveyor control  
LED strobe light  
8' (2.4 m) or 10' (3 m) broom  
Spray down system  
Work lights (3)  
Premium LED work lights (5)  
DC blade lights  
Remote strike-off  
2,300 lb (1043 kg) counterweight  
12 kW generator  
Grade and slope prep  
Opposite side hydraulics  
1' (.3 m), 2' (.6 m), 3' (.9 m), 6' (1.8 m) strike-off tools  
2' - 3' (.6 - .9 m), 3' - 5' (.9 - 1.5 m) telescoping strike-off tool

## WARRANTY

12 months standard. Extended warranty available.