

B570

WHEEL FELLER BUNCHER



ENHANCED TRAVEL & SAW RECOVERY.

The patented Power Direct Plus system optimizes performance by focusing power where the operator demands. The hydraulic pumps are oversized providing greater overall capacity and improved travel power and saw recovery.



ROCK SOLID STABILITY.

The patented transverse mounted engine design and low center of gravity provide rock solid stability. Superior stability delivers market leading cut and carry capability to build larger, easy to reach bundles improving skidder efficiency.



APPLICATION VERSATILITY.

The balance of a short wheelbase, power, stability and agility provides superior application versatility allowing seamless transitions from 1st thinnings to final fell applications. Versatility maximizes long term value as markets fluctuate.



OPERATOR COMFORT.

A quiet and spacious cab with a powerful HVAC system and rear view camera keep operators comfortable and productive. The premium seat with more leg room near the joystick mounts and overall machine balance provide a superior ride.



EXCELLENT SERVICEABILITY.

Pressurized engine, hydraulic and after treatment compartments keep debris out of the machine reducing down time for clean out. Ground level fuel fill, electric hydraulic oil fill pump and superior engine access deliver excellent serviceability.



GREATER DURABILITY & RELIABILITY.

The field proven cooling system keeps the engine and hydraulics cool, extending component life. Robust frames with integrated steering cylinder mounts and field proven hitch for nearly 20 years are built for the harshest applications.

B570 SPECIFICATIONS

Engine Model	Cat® C7.1 Tier 4 Final		Wheelbase	110.0"	2794 mm	Ground Clearance	19.4"	493 mm
Gross Power	203 hp	151 kW	Fuel Capacity	81.6 gal	309 L	Transport Width	9' 7"	2.92 m
Engine Speed	1880 rpm		DEF Capacity	5.0 gal	19 L	Transport Height	10' 5"	3.17 m
Weight	39,120 lb	17 744 kg	Hydraulic System	64.2 gal	243 L	Transport Length	24' 9"	7.55 m

Base configuration includes 28L-26 16PR Tires and 232 High Capacity Bunching Saw. Weight add 1,720 lb (780 kg) for 30.5L-32 tires, 2,560 lb (1161 kg) for 30.5L-32 2X Ring tires, 1,720 lb (780 kg) for 67-34 tires. Height and ground clearance add 4.0" (10.2 cm) for 30.5L-32 tires, 1.1" (2.8 cm) for 67-34 tires.

POWERTRAIN

Cat C7.1 engine certified to EPA Tier 4 Final
Primary and secondary fuel filters, including water separator
Electric fuel priming pump
Electric fuel transfer pump
Centrifugal engine air pre-cleaner
2-Stage engine air cleaner
Cross-flow cooling system with side by side cores
Swing out air conditioner condenser and fuel cooler
Hydraulically driven, on demand reversing cooling fan
Electronically driven, reversing pressurizing fan
2-Speed, manually shifted transmission
Cat HD axles, approved for odd size dual tires up to 30.5L-32 with 24.5L-32 and wide tires up to 73-44
Momentary front differential lock
On/off rear differential lock
Heavy-duty driveshafts
Lubed for life universal joints
Spring applied, hydraulically released parking brake

OPERATOR ENVIRONMENT

Enclosed OPS/FOPS/ROPS certified cab
Reverse slope 3-piece windshield
High capacity HVAC system
Pressurized water tank
Air suspension seat with harness seat belt
Joystick steering controls
Joystick gather arm(s) controls
Foot pedal gather arm(s) controls ready only
AM/FM/Bluetooth Radio
Rear view camera
24V to 12V converter and 2 12V power ports
2 Beverage holders
Advanced Operator Controls
Operator control adjustability
Terrain Selection Mode
Creep Mode
Road Steer Mode
Computerized Monitoring System

HYDRAULICS

PowerDirect Plus System
Load-sense hydraulics
Variable displacement pumps
High performance, multi-functioning main control valve
Dual inline, spin on return filters
Electric hydraulic oil fill pump

ELECTRICAL

130 ampere alternator
24-volt electrical system with 2 12-volt batteries
Main disconnect switch with Diesel Exhaust Fluid (DEF) purge indicator light
6 halogen working lights
Product Link™ Ready

OTHER STANDARD EQUIPMENT

Heavy-duty double walled box section frames
Dual tapered roller bearing upper and lower center hitch
Pins, Chrome plated lift arm and tilt pins
Ecology drains (engine oil, engine coolant, hyd tank, fuel tank, axles)
Tilt Cab
Pressurized engine, hydraulic and CEM compartments
Ground level fuel fill
Remote mounted test ports
Single side engine service
S-O-S sampling ports

OPTIONAL EQUIPMENT

221 Center Post Felling Saw - 22.7" (576 mm)
232 High Capacity Bunching Saw - 22.6" (573 mm)
222SC Side Cut Felling Saw - 22.0" (560 mm)
28L x 26 NOAW Tires - Overall Width 9' 2" (2.79 m)
28L x 26 Tires - Overall Width 9' 7" (2.92 m)
30.5L x 32 NOAW Tires - Overall Width 9' 9" (2.98 m)
30.5L x 32 Tires - Overall Width 10' 4" (3.16 m)
30.5L x 32 2X Ring Tires - Overall Width 9' 9" (2.98 m)
67 x 34 Tires - Overall Width 10' 7" (3.22 m)

SALES AND SERVICE

Sold and serviced exclusively through Weiler Forestry dealers worldwide

WARRANTY

12 months standard, extended warranty available